

The "Transporter Combo Drop" from Viking Specialized Trailers combines the quality and durability that goes into every trailer. Aluminum crossmembers, outriggers, side rail, bulkheads and flooring come together to make our lightest Drop Deck trailer produced. This trailer was designed to last and allow you to haul the most. The Viking "Transporter Combo Drop" new ideas and innovation at work for you. Capacity: 80,000 lb. GVWR.





Transporter Combo Drop Deck Model: VDHC48102T 48'-0" 10'-6" 37'-6"-17 1/2" -24"-48" $(\hat{\mathbf{\varphi}})$ ॑॑॑॑ 40 3/4" 102" Wide Weight 11,000 lbs. Plus or Minus 3% Capacity: 80,000 lb. GVWR

Features:		
•	Mainframe	24" Fabricated main beams with 2" camber, $1/2$ " x 5" top and bottom flange, $5/8$ " x 5" bottom flange in the neck, $3/16$ " web welded on both sides with weight reduction holes. All flange and web material is high strength steel.
•	Kingpin	4" Extruded aluminum I beam on 16" centers with single coil package. 2" SAE kingpin, 1/4" plate, 24" kingpin setting (standard).
•	Siderails	6" Extruded aluminum with stake pockets on 24" centers. 3/8" x 3" Aluminum rubrails with double pipe spools.
•	Suspension	(2) Hendrickson® INTRAAX AAL 25K unitized air ride suspension (dump valve included on rear axle).
•	Axles	(2) 25,000 Lb., 5-3/4" round, (included with suspension).
٠	Brakes	16-1/2" x 7", Type 30/30 brake chambers, outboard drums, Meritor WABCO® (2S/1M) ABS on one axle.
•	Wheels	8.25 x 22.5, Aluminum, 10 Hole disc, hub piloted (polished finish on the outside and machine finish on the inside).
•	Tires	255/70R x 22.5 Radials.
•	Landing gear	2 Speed gear with 62,500 lb. lift capacity; 200,000 lb. static capacity (standard).
•	Finish	Steel components are shotblasted, epoxy primed and painted with a high solid polyurethane paint. Colors: black or red (standard) optional colors available.
٠	Floor	1-1/4" Extruded aluminum with 4 apitong nailing strips.
•	Lights	7-Way main receptacle, sealed wiring harness with 3 red (tail / stop / turn) rubber mounted LED lights with a 3 light center cluster, 5 clearance lights per side including mid-turn.
•	Tandem	10' 1" Spread axle set from the rear of the trailer (Optional settings available).
•		(12) Sliding winches on winch track, (2) on upper deck, (10) on lower deck located on the roadside.
•	Rear bumper	DOT certified rear under ride guard/bumper with high visibility reflective conspicuity tape and rubber dock bumpers.

Options:

- Spring or air ride slider
- Spring suspension
- Spare tire carrier
- 18" x 18" x 60" Aluminum Tool box
- 48" Front bulkhead
- Longer and shorter lengths
- Front and rear stake pockets

Viking Specialized Trailers, L.L.C. 1730 S.W. Stalling Dr., Suite 101 Nacogdoches, Texas 75964 (936) 564-8370 (844) 815-6210 Fax (936) 205-9171 www.vikingspzdtrailers.com